



Oil Content Analyzer **OCMA-550**



550

For measurement of
Residual oil on components

Oil Content Analyzer OCMA-550



OCMA-550 to measure residual oil on components and concentrations of oil adhered on solids such as soil. Measurement can be easily made only by injecting the extracted water sample into the attached cell and setting it to the equipment. This model features a simple design which allows opening/closing of the door to setting of cell with just one hand. This is best for measurement of extracted samples such as evaluation of residual oil on components and measurement of oil contained in food.



Feature

■ Cell is easily detachable with just one hand

Simple design which allows opening/closing of door and detachment of cell with just one hand. Measurement operation becomes smoother.



■ Timer function


A timer function to display a measurement value in a certain amount of time is equipped. This saves work and time required for measurement.




Residual oil on components
For quality control of components



For piping of air conditioners and refrigerators
To prevent reduction of cooling function



Semiconductor field
For evaluation of degreasing capacity



Others
Useful for soil (environmental pollution), food (health hazard) and gas (quality deterioration)

Automatic operation with one switch

Compact oil content analyzer OCMA-500 series.
Operability is significantly improved while user-friendly features of the conventional products are maintained as they are.


This machine is easy for anyone to use because all you have to do is press a button.

This can be utilized across wide variety of applications such as drain monitoring and quality control for components.

Easy and speedy measurement for approx. 3 minutes*1

Measurement can be easily made in a short time only by pressing the start button. Measurement time can be significantly reduced in comparison with the n-hexane extraction method.

*Excluding time for warming and calibration.



*1 Shortest time. Measurement time depends on quality of sample.

*2 In case of OCMA-500. Put extracted sample into the cell to set in case of OCMA-550.

Any oil with low boiling point can be measured

The n-hexane extraction method needs to evaporate solvent and any oil with a low boiling point (toluene, gasoline, etc.) is evaporated along with solvent. The OCMA-500 series does not need to evaporate solvent, preventing evaporation of these kinds of oil.




What is the n-hexane extraction method?

Testing method used to measure oil components. Because oil of a low-boiling component such as gasoline or toluene is volatilized, an error may occur if they are included. It is necessary to take note of them when making evaluations.

Improvement of operability

Color graphic liquid crystal

It is easier to see menu and measurement results because a 3.5 inch color graphic (LCD) is employed.



USB data output port

It is easy to control data in a personal computer by saving data in a USB memory.

*A format supports USB of FAT/FAT32. HORIBA recommended USB is available.



Date	Value	Unit	Value(Raw)	Unit(Raw)	Status	Memo
2018/02/23 11:17	79.6	mg/L	79.6	mg/L	2	sample01
2018/02/23 11:22	100	mg/L	100	mg/L	0	sample02
2018/02/23 14:05	181	mg/L	181	mg/L	0	sample03
2018/02/23 15:58	98.6	mg/L	98.6	mg/L	0	sample04
2018/02/26 10:19	2	mg/L	2	mg/L	0	sample05
2018/02/26 16:39	6.8	mg/L	6.8	mg/L	0	sample06
2018/03/24 14:41	1.9	mg/L	1.9	mg/L	0	sample07
2018/03/24 17:57	125	mg/L	125	mg/L	0	sample08
2018/03/24 18:17	3.8	mg/L	3.8	mg/L	0	sample09
2018/03/25 15:58	110	mg/L	110	mg/L	0	sample10
2018/03/25 16:17	199	mg/L	199	mg/L	0	sample11
2018/03/26 10:07	0.7	mg/L	0.7	mg/L	0	sample12
2018/03/26 11:40	169	mg/L	169	mg/L	0	sample13

Output data (reference)

Unit conversion function

Indication unit (mg/L, mg/kg, mg/g, mg/PC, Abs (OCMA-550)) can be changed according to the purpose by inputting the measurement conditions.

Multi-language function

Japanese, English, Russian, Chinese, Korean, German and French languages are available. Each language can be selected from the screen menu.




How to measure by OCMA

The OCMA-500 series extracts the oil components contained in a measurement sample into solvent (S-316) to measure the oil content with an IR analyzer.

*Carry out pre-washing for correct measurement.

*In case of OCMA-500



※ OCMA-500/550 may not be able to measure some samples containing protein, surfactant, hydrophilic organic solvent and others. Please ask your local dealer before purchasing when considering these kind of samples.



Oil Content Analyzer

OCMA-500

■ Standard Accessory

Filter element	For water filter, diameter 40 mm, including 5 elements
Dropper	Made of polyethylene, 2.5 mL
Code set	Power supply cable (for domestic use)
B heavy oil	10 mL
Instruction manual	OCMA-500
Water absorptive sheet	Liquid tray from extraction tank

■ Option

Oil extracted solvent	S-316
Measuring Syringe set (Simple type)	Micro Syringe 25 μ L Measuring Syringe (For Sample) 20 mL Measuring Syringe (For Solvent) 10 mL
Measuring Syringe set (Standard type*)	Micro Syringe 25 μ L Measuring Syringe (For Sample) 20 mL Measuring Syringe (For Solvent) 20 mL
Packing	For water filter For extraction tank
Solvent Reclaimer	SR-305

*Measuring is easy because with stopper.



Oil Content Analyzer

OCMA-550

■ Standard Accessory

Dropper	Made of polyethylene, 2.5 mL
Code set	Power supply cable (for domestic use)
B heavy oil	10 mL
Instruction manual	OCMA-550
Cell	Quartz (20 mm): 1 piece
Cell cap	Cap for cell: 1 cap

■ Option

Oil extracted solvent	S-316
Measuring Syringe set (Simple type)	Micro Syringe 25 μ L Measuring Syringe (For cell injection) 10 mL
Solvent Reclaimer	SR-305


For the first purchase customer

In order to measure oil content with OCMA-500 series, you need the following products. If you don't have these products, please purchase from optional list.


Must items for measurement		Recommended options (Not including maintenance parts)	
Standard Set	Solvent	Measuring Syringe set	Solvent Reclaimer
OCMA-500  + Standard Accessory	S-316 	Standard type (with Stopper)  *Choose from standard type or simple type	SR-305  Designed especially for recycling S-316 solvent, it features a 2- layer column of activated carbon and aluminum
OCMA-550  + Standard Accessory		Simple type 	

■ Dimensional Outline (Unit: mm)

OCMA-500



OCMA-550



■ Specifications

	OCMA-500	OCMA-550
Measurement method	Solvent extraction – non-dispersive infrared absorption analysis method	
Measured objects	Substances extracted from sample water into solvent and having infrared absorption near a wavelength from 3.4 μm to 3.5 μm	
Measurement range	0 mg/L to 200 mg/L	
Resolution	For mg/L 0 to 99.9: 0.1, 100 to 200: 1	
Repeatability	0 mg/L to 9.9 mg/L: ±0.3 mg/L 10.0 mg/L to 99.9 mg/L: ±2.1 mg/L 100 mg/L to 200 mg/L: ±5 mg/L *For standard liquids at constant temperature	0 mg/L to 9.9 mg/L: ±0.5 mg/L 10.0 mg/L to 99.9 mg/L: ±2.1 mg/L 100 mg/L to 200 mg/L: ±5 mg/L *For standard liquids at constant temperature
Display method	3.5 inches 320×240 dots Backlight color graphic LCD	
Calibration method	Select each optionally zero calibration and span calibration.	
Amount of test sample required	2:1 (Sample water : Solvent)	—
Extraction solvent	S-316 *Do not use any other solvent than S-316.	
Amount of extraction solvent required	8 mL (possible to measure even at 10mL)	Approx. 6.5 mL (Amount of extraction solvent required)
Extraction method	Built-in extractor	Using the extraction solvent, and extracted manually outside the product
Ambient operating temperature	0°C to 40°C (no condensation)	
Power supply	AC 100 V to 240 V ±10%, 50/60 Hz	
Power consumption	AC 100 V: Approx. 60 VA, AC 240 V: Approx. 90 VA	AC 100 V - 240 V: Approx. 60 VA
External dimensions	342 (H) X 200 (W) X 313 (D) mm	195 (H) X 253 (W) X 293 (D) mm
Mass	Approx. 7 kg	Approx. 5 kg
External output	Output to a USB memory stick	
Measurement flow	Automatic measurement (automatic switching sequence) and manual measurement after injection of liquid	—
Cell length	—	20 mm
Cell material	—	Quartz
Functions	300-item data memory (measurement history) Self-error determination Stabilized measurement value display Clock function With backlight for stirred batch tank Unit conversion function Compliant with ASTM D7066-4	300-item data memory (measurement history) Self-error determination Stabilized measurement value display Clock function Unit conversion function Compliant with ASTM D7066-4



The HORIBA Group adopts IMS (Integrated Management System) which integrates Quality Management System ISO9001, Environmental Management System ISO14001, and Occupational Health and Safety Management System OHSAS18001.
We have now integrated Business Continuity Management System ISO22301 in order to provide our products and services in a stable manner, even in emergencies.



Please read the operation manual before using this product to assure safe and proper handling of the product.



- The specifications, appearance or other aspects of products in this catalog are subject to change without notice.
- Please contact us with enquiries concerning further details on the products in this catalog.
- The color of the actual products may differ from the color pictured in this catalog due to printing limitations.
- It is strictly forbidden to copy the content of this catalog in part or in full.
- The screen displays shown on products in this catalog have been inserted into the photographs through compositing.
- All brand names, product names and service names in this catalog are trademarks or registered trademarks of their respective companies.

HORIBA

Head Office
2 Miyahonogashi-cho, Kisshoin Minami-ku, Kyoto, Japan
Phone: 81 (75) 313-8123 Fax: 81 (75) 321-5725
<http://www.horiba.com>

Manufactured by
HORIBA Advanced Techno

HORIBA (China) Trading Co., Ltd. China

Unit D, 1F, Building A, Synnex International Park, 1068 West Tianshan Road, Shanghai, 200335, China
Phone: 86 (21) 6289-6060 Fax: 86 (21) 6289-5553

Beijing Office

12F, Metropolis Tower, No.2, Haidian Dong 3 Street, Beijing, 100080, China
Phone: 86 (10) 8567-9966 Fax: 86 (10) 8567-9066

HORIBA (Thailand) Limited Thailand

East Office
850 / 7 Soi Lat Krabang 30 / 5, Lat Krabang Road, Lat Krabang, Bangkok 10520, Thailand
Phone: 66 (0) 2734 4434 Fax: 66 (0) 2734 4438

HORIBA Instruments (Singapore) Pte Ltd. Singapore

3 Changi Business Park Vista #01-01 Akzonobel House, Singapore 486051
Phone: 65 (6) 745-8300 Fax: 65 (6) 745-8155

HORIBA Vietnam Co., Ltd. Vietnam

Unit 6, 10 Floor, CMC Tower, Duy Tan Street, Dich Vong Hau Ward, Cau Giay District, Hanoi, Vietnam
Phone: 84 (24) 3795-8552 Fax: 84 (24) 3795-8553

PT HORIBA Indonesia Indonesia

Jl. Jalur Sutera Blok 20A, No.16-17, Kel. Kunciran, Kec. Pinang Tangerang-15144, Indonesia
Phone: 62 (21) 3044-8525 Fax: 62 (21) 3044-8521

HORIBA KOREA Ltd. Korea

25, 94-Gil, Iljik-Ro, Manan-Gu, Anyang-Si, Gyeonggi-Do, 13901, Korea
Phone: 82 (31) 296-7911 Fax: 82 (31) 296-7913

HORIBA India Private Limited India

246, Okhla Industrial Estate, Phase 3 New Delhi-110020, India
Phone: 91 (11) 4646-5000 Fax: 91 (11) 4646-5020

Technical Center

D-255, Chakan MIDC Phase-II, Bhamboli Village, Pune-410501, India
Phone: 91 (21) 3567-6000

Bangalore Office

No.55, 12th Main, Behind BDA Complex, 6th sector, HSR Layout, Bangalore South, Bangalore-560102, India
Phone: 91 (80) 4127-3637

HORIBA Instruments Incorporated USA

9755 Research Drive, Irvine, CA 92618, U.S.A.
Phone: 1 (949) 250-4811 Fax: 1 (949) 250-0924

Houston Office

5390 Bay Oaks Drive, Pasadena, TX 77505
Phone: 1 (281) 482-4334 Fax: 1 (281) 674-6058

HORIBA Instruments Brasil, Ltda. Brasil

Rua Presbitero Plinio Alves de Souza, 645, Parte A, Loteamento Multivias, Jardim Ermita II - Jundiá São Paulo - CEP 13.212-181 Brazil
Phone: 55 (11) 2923-5400 Fax: 55 (11) 2923-5490

HORIBA Europe Research Center France

Avenue de la Vauve - Passage Jobin Yvon CS 45002 - 91120 Palaiseau - France
Phone: 33 (1) 69-74-72-00 Fax: 33 (1) 69-31-32-20

HORIBA UK Limited UK

Kyoto Close Moulton Park, Northampton NN3 6FL, UK
Phone: 44 (1604) 542-500 Fax: 44 (1604) 542-699

HORIBA Europe GmbH Germany

Hans-Mess-Str.6 D-61440 Oberursel Germany
Phone: 49 (6172) 1396-0 Fax: 49 (6172) 1373-85

Leichlingen Office

Julius-kronenberg Str.9 D-42799 Leichlingen Germany
Phone: 49 (2175) 8978-0 Fax: 49 (2175) 8978-50

HORIBA Czech Czech

Prague Office

Prumyslova 1306 / 7, CZ-10200, Praha 10, Czech Republic
Phone: 420 (2) 460-392-65

HORIBA (Austria) GmbH Austria

Kaplanstrasse 5 A-3430 Tulln, Austria
Phone: 43 (2272) 65225 Fax: 43 (2272) 65230

HORIBA (Austria) GmbH Romania

Romania Branch

B-dul.Republicii, nr. 164, Etaj Parter, Birourile nr. 3 si 4 Pitestijudetul Arges110177 Romania
Phone: 40 (348) 807117 Fax: 40 (348) 807118

Bulletin:HAE-T0254B

Printed in Japan 1903SK23